



Modeling framework for multi-enzyme in-pot processes applied in amine production

Andrade Santacoloma, Paloma de Gracia; Sin, Gürkan; Gernaey, Krist; Woodley, John

Publication date:
2011

Document Version
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):
Andrade Santacoloma, P. D. G., Sin, G., Gernaey, K., & Woodley, J. (2011). *Modeling framework for multi-enzyme in-pot processes applied in amine production*. Abstract from Biotrans 2011, Giardini Naxos, Italy.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Modeling framework for multi-enzyme in-pot processes applied in amine production

Paloma A. Santacoloma^a, Gürkan Sin^b, Krist V. Gernaey^a, John M. Woodley^a

^aPROCESS; ^bCAPEC; Department of Chemical and Biochemical Engineering, Technical University of Denmark, Søltofts Plads, Building 229, DK-2800 Kgs. Lyngby
E-mail: psa@kt.dtu.dk

Nowadays multi-enzyme processes are seen as an alternative to assist in the synthesis of complex compounds of industrial interest [1]. In general, a multi-enzyme in-pot process is characterized by the mixture of enzymes that catalyze several reactions in a single pot. In this manner, purification steps of intermediate products may be eliminated. Consequently, it potentially leads to considerable process improvements like increases in the process yield, and reduction in downstream processing and operating costs [2]. In the analysis of these types of processes, mathematical models and computational tools enable a systematic development of multi-enzyme in-pot processes [3].

The aim of this contribution is to present a methodological framework for modeling multi-enzyme in-pot processes in order to formulate reliable models for further applications e.g. optimization, control, prediction. Additionally, the methodology is exemplified stepwise through the production of amines by combining the action of three enzymes in a single reactor [4]. In the applied method, amines are synthesized from ketones by using the first enzyme (transaminase, E.C. 2.6.1.2) together with L-alanine which provides the amino donor (see figure 1). The generated pyruvate, from the first reaction, is reduced by the second enzyme (lactate dehydrogenase, LDH, E.C. 1.1.1.27) to L-lactate. Removing the pyruvate contributes to both driving the reaction to completion and eliminating pyruvate inhibition of the transaminase. The third enzyme (glucose dehydrogenase, GDH, E.C. 1.1.1.47) is added to the system in order to recycle the NADH cofactor [5].




Figure 1. Reaction scheme for the synthesis of amines by applying a three-enzymatic in-pot process (transaminase, LDH and GDH)

- [1] Bruggink, A., Schoevaart, R. and Kieboom, T. *Org. Process Res. Dev.* 2003, 4, 622
- [2] Santacoloma, P.A., Sin, G., Gernaey, K.V. and Woodley, J.M. *Org. Process Res. Dev.* 2011, 15, 203
- [3] Morales-Rodriguez, R. and Gani, R. *Computer Aided Chemical Engineering*, 2007, 24, 207
- [4] Koszelewski, D., Lavandera, I., Clay, I., Guebitz, G.M., Rozzell, D. and Kroutil, W. *Adv. Synth. Catal.* 2008, 350 (17), 2761
- [5] Truppo, M.D., Rozzell, J.D. and Turner, N.J. *Org. Process Res. Dev.* 2010, 14, 234